DROWNFIRE PRIVATE LIMITED
Sarvoday, RH-2, opp. Copa Villa Restaurant, Madhuban Colony, Jagtap Dairy, PCMC,
Pimpri-Chinchwad, Pune, Maharashtra 411027
+91 72 4747 6161 · sales@firespray.in · www.firespray.in
GSTIN 27AAKCD6292J1Z4

Clean Agent Fire Extinguisher

Clean agent fire extinguisher for electrical panels, servers and electronics. No residue, safe on sensitive equipment. ISI marked.



PRODUCT DATA

Product	Clean Agent Fire Extinguisher
SKU	FS-CA
Sizes	2 kg, 4 kg, 6 kg
Category	Clean Agent Fire Extinguisher
Standard	ISI marked, IS 15683:2018 (BIS)
Delivery	Pan-India, dispatch within 7 days, GST invoice, freight extra
Replacement	10 days for a manufacturing fault or transit damage

SPECIFICATIONS (AS PRINTED ON OUR CLEAN AGENT LABEL)

Extinguishing agent	Clean agent (HCFC-123 / FE-36)
Fire classes on label	A, B, C (electrical equipment)
Operating pressure	12 bar
Discharge time	10 to 15 seconds
Effective range	3 to 5 metres
Temperature range	-20 °C to +60 °C
Mark	ISI marked, BIS approved

WHICH SIZE

Size	Good for
2 kg	Small panels, DBs, cabins, single server racks
4 kg	Electrical rooms, UPS rooms, control rooms
6 kg	Larger panel rooms, server halls, labs

SUITABLE FOR

- Class A: wood, paper, cloth, plastic and other solids, such as cable insulation, files and furniture in a control room.
- Class B: flammable liquids such as petrol, diesel, oil, paint and solvents.
- Class C and electrical: live electrical equipment, sensitive electronics and server rooms.

Spec sheet for quotation and tender use. Prices are not included; ask for a GST quotation at sales@firespray.in or on WhatsApp +91 72 4747 6161.
Product page: https://firespray.in/p/fire-extinguisher-for-electrical-panel/